

10/585914

- 1 -

AP20 Rec'd PCT/PTO 13 JUL 2006

~~DESCRIPTION~~

DIFFERENTIAL DRIVE CIRCUIT AND  
ELECTRONIC APPARATUS INCORPORATING SAME

5

TECHNICAL FIELD

The present invention relates to a differential drive circuit for an LVDS (Low-Voltage Differential Signals) interface that transmits signals by changing a direction of flow of the electric current in a pair of resistor-terminated differential transmission lines, and an electronic apparatus incorporating the differential drive circuit.

15 BACKGROUND ~~ART~~ OF THE INVENTION

For a differential drive circuit for an LVDS interface, the one described in the patent document 1 as set forth below is known. A drive circuit suggested herein employs a configuration in which by using three differential amplifiers a differential voltage is changed while the offset potential is kept constant. Hence, there are problems that the circuit becomes complicated, increasing the circuit area and the total current consumption, and two differential amplifiers that drive transistors of the final stage are likely to cause oscillation, which is triggered by power supply noise or the like. Furthermore, with a drive circuit capability,

the one described in the patent document 2 as set forth below is known. A drive circuit proposed herein is composed of a main drive circuit and a pre-emphasis circuit and both circuits are biased by a current source. Hence,  
5 the circuit tries to supply a constant current regardless of changes or variations in load and thus the voltage ( $V_{SD}$ ) between a source and a drain changes with respect to changes in the load; as a result, the common-mode voltage is not stabilized. Especially in a standby state, the  
10 circuit falls in a situation where the trouble of EMI is likely to occur, and thus, there is a problem of noise trouble associated with high-speed drive.

Patent Document 1: Publication of USP6,111,431

Patent Document 2: Publication of USP6,590,432

15

~~DISCLOSURE OF THE INVENTION~~

~~PROBLEMS TO BE SOLVED BY THE INVENTION~~

The present invention is made with a view to solving such problems. An object of the present invention  
20 is, therefore, to provide a differential drive circuit for low voltage differential signals, in which, by eliminating differential amplifiers or reducing the number of differential amplifiers, the circuit area and current consumption may be reduced and the problem of oscillation  
25 caused by noise may be solved, and by stabilizing the common-mode level, an occurrence of trouble of the EMI may be reduced and a high drive capability is provided, and an

electronic apparatus incorporating therein such a circuit.

~~MEANS FOR SOLVING PROBLEMS~~ SUMMARY OF THE INVENTION

According to a claim 1, there is provided a  
5 differential drive circuit for low voltage differential  
signals, which comprises:

a switching circuit including MOS transistors, and  
configured to be inputted thereto with differential signals  
and to output therefrom current signals;

10 an output circuit including an NMOS transistor  
connected at its one end to a power supply potential on a  
high potential side and at its other end to one node of the  
switching circuit, and operating as a source follower; and  
a PMOS transistor connected at its one end to a power  
15 supply potential on a low potential side and at its other  
end to the other node of the switching circuit and  
operating as a source follower; and

a reference potential generating circuit that  
supplies reference potentials to gates of the NMOS  
20 transistor and the PMOS transistor, respectively, wherein

the reference potential generating circuit  
includes potential variable means for changing a  
differential potential with an offset potential being kept  
constant.

25 According to a claim 2, in the differential drive  
circuit for low voltage differential signals according to  
claim 1,

the switching circuit may include a first transistor and a second transistor connected at their one ends to a source of the NMOS transistor, forming a node; a third transistor and a fourth transistor connected at their one ends to a source of the PMOS transistor, forming a node,

a node at which the first transistor and the third transistor are connected at their other ends and a node at which the second transistor and the fourth transistor are connected at their other ends form output terminals of the output circuit, and

a node at which the first transistor and the fourth transistor are connected at their gates and a node at which the second transistor and the third transistor are connected at their gates form input terminals for the differential signals.

According to a claim 3, in the differential drive circuit for low voltage differential signals according to the claim 1, the reference potential generating circuit may include:

a first resistor connected between the power supply potential on the high potential side and the gate of the NMOS transistor;

a second resistor connected between the gate of the NMOS transistor and the gate of the PMOS transistor; and

a third resistor connected between the gate of the PMOS transistor and the power supply potential on the low

potential side.

According to a claim 4, in the differential drive circuit for low voltage differential signals according to the claim 3,

5 the first resistor and the third resistor in the reference potential generating circuit may have an equal resistance value.

According to a claim 5, in the differential drive circuit for low voltage differential signals according to  
10 the claim 1,

the reference potential generating circuit may include:

a first circuit group configured to have a plurality of series-connected PMOS transistors and a  
15 plurality of series-connected resistors, which are connected in parallel;

a second circuit group configured to have a plurality of series-connected NMOS transistors and a plurality of series-connected resistors, which are  
20 connected in parallel; and

a resistor connected between the resistors in the first circuit group and the resistors in the second circuit group, and

the resistors in the first circuit group and the  
25 resistors in the second group may be set to an equal resistance value, where the resistance value may be changed by controlling gates of the transistors in the first and

the second circuit groups.

According to a claim 6, in the differential drive circuit for low ~~potential~~<sup>voltage</sup> differential signals according to claim 1, the reference potential generating circuit may  
5 include:

a first circuit group which further includes:

a first NMOS transistor connected at its drain to the power supply potential on the high potential side;

a second NMOS transistor connected at its drain  
10 to a source of the first NMOS transistor and at its gate to the power supply potential on the high potential side;

a third NMOS transistor connected at its source to the power supply potential on the low potential side;

a fourth NMOS transistor connected at its  
15 source to a drain of the third NMOS transistor and at its gate to the power supply potential on the high potential side;

a first resistor and a second resistor connected between a source of the second NMOS transistor  
20 and a drain of the fourth NMOS transistor;

a first differential amplifier having an output terminal connected to gates of the first NMOS transistor and a fifth NMOS transistor and controlling potentials of the gates, and operating such that a potential of a node at  
25 which the first resistor and the second resistor are connected approximates a first reference potential; and

~~the~~  $\sqrt{\frac{a}{I}}$  current source variable means that controls

a current of the third NMOS transistor connected at its source to the power supply potential on the low potential side; and

a second circuit group which further includes:

5           the fifth NMOS transistor connected at its drain to the power supply potential on the high potential side;

          a sixth NMOS transistor connected at its drain to a source of the fifth NMOS transistor and at its gate to  
10       the power supply potential on the high potential side, and

          a seventh PMOS transistor connected at its drain to the power supply potential on the low potential side;

          an eighth NMOS transistor connected at its  
15       source to a source of the seventh PMOS transistor and at its gate to the power supply <sup>potential</sup> on the high potential side, and

          a third resistor and a fourth resistor connected between a source of the sixth NMOS transistor and  
20       a drain of the eighth NMOS transistor; and

          a second differential amplifier having an output terminal connected to a gate of the seventh PMOS transistor and controlling a potential of the gate, and operating such that a potential of a node at which the  
25       third resistor and the fourth resistor are connected approximates the first reference potential.

According to a claim 7, in the differential drive

circuit for low voltage differential signals according to the claim 6,

resistance values of the first resistor, the second resistor, the third resistor, and the fourth resistor in the reference potential generating circuit may  
5 be  $n/2$  ( $n$  is a positive integer value) times a resistance value of a terminating resistor connected to output terminals of the output circuit.

According to a claim 8, in the differential drive  
10 circuit for low voltage differential signals according to the claim 6,

a size of the first NMOS transistor and that of the fifth NMOS transistor of the reference potential generating circuit may be  $1/n$  ( $n$  is a positive integer  
15 value) of a size of the NMOS transistor, and

a size of the seventh PMOS transistor may be  $1/n$  ( $n$  is a positive integer value) of a size of the PMOS transistor.

According to a claim 9, in the differential drive  
20 circuit for low voltage differential signals according to the claim 1,

output terminals of the output circuit may be connected to output terminals of an emphasis circuit,

the emphasis circuit may include a switching  
25 circuit for the emphasis circuit including MOS transistors, to which different differential signals are inputted and which output current signals, one node in the switching



circuit for the emphasis circuit being connected to a drain of a PMOS transistor, a source of the PMOS transistor being connected to the power supply potential on the high potential side, and a gate of the PMOS transistor being  
5 connected to one terminal of a bias power supply for the emphasis circuit, and

the other node of the switching circuit for the emphasis circuit may be connected to a drain of an NMOS transistor, a source of the NMOS transistor may be  
10 connected to the power supply <sup>potential</sup> on the low potential side, and a gate of the NMOS transistor may be connected to other terminal of the bias power supply for the emphasis circuit.

According to a claim 10, in the differential drive circuit for low voltage differential signals according to  
15 the claim 9,

the switching circuit for the emphasis circuit may be constituted by the switching circuit according to the claim 2.

According to claim 11, in the differential drive circuit for low voltage differential signals according to  
20 the claim 9, the emphasis circuit may be configured in a manner such that:

one node of the switching circuit for the emphasis circuit is connected to a source of an NMOS transistor, a  
25 drain of the NMOS transistor is connected to the power supply on the high potential side, and a gate of the NMOS transistor <sup>potential</sup> is connected to one terminal of a bias power

supply for the emphasis circuit; and

the other node of the switching circuit for the emphasis circuit is connected to a source of a PMOS transistor, a drain of the PMOS transistor is connected to the power supply <sup>potential</sup> on the low potential side, and a gate of the PMOS transistor is connected to the other terminal of the bias power supply for the emphasis circuit.

According to a claim 12, in the differential drive circuit for low voltage differential signals according to the claim 11,

the switching circuit for the emphasis circuit may be constituted by the switching circuit according to the claim 2.

According to a claim 13, there is provided an electronic apparatus, which comprises a differential drive circuit for low voltage differential signals according to any one of the claims 1 through 12.

According to a claim 14, in the electronic apparatus according to the claim 13, the electronic apparatus may be constituted by a mobile terminal.

#### ~~EFFECT OF THE INVENTION~~

According to the differential drive circuit for low voltage differential signals of the present invention, it is possible to provide a differential drive circuit for low voltage differential signals by which reduction in the circuit area and current consumption may be achieved so as

to solve the problem of oscillation caused by noise, and occurrence of the trouble of EMI may be reduced due to stabilizing of the common-mode level to thereby provide a high drive capability. Also, it is possible to provide an  
5 electronic apparatus incorporating therein such a differential drive circuit as described above.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a circuit block diagram showing a  
10 configuration of a differential drive circuit of a first embodiment according to the present invention.

FIG. 2 is a circuit block diagram showing a configuration of a reference potential generating circuit of the first embodiment according to the present invention.

15 FIG. 3 is a diagram of a reference potential generating circuit having variable resistors, according to the present invention.

FIG. 4 is a diagram of a reference potential generating circuit having a potential variable means,  
20 according to the present invention.

FIG. 5 is a diagram of a reference potential generating circuit having another potential variable means, according to the present invention.

FIG. 6 is a circuit block diagram showing a  
25 configuration of a differential drive circuit of a second embodiment according to the present invention.

FIG. 7 is a diagram showing input/output signal

trains for the differential drive circuit of the second embodiment according to the present invention.

FIG. 8 is a diagram showing other input/output signal trains for the differential drive circuit of the second embodiment according to the present invention.

FIG. 9 is a diagram showing input/output signal trains for a differential drive circuit using another emphasis circuit, according to the present invention.

10 ~~DESCRIPTION OF THE REFERENCE NUMERALS~~

~~1-6, 41-44, 49-52, and 61-66: TRANSISTOR~~

~~45, 46, 53, and 54: RESISTOR~~

~~7, 8, 11, 12, 21, 22, and 71-74: NODE~~

~~9, 10, 69, and 70: DIFFERENTIAL INPUT TERMINAL~~

15 ~~13, 14: POWER SUPPLY POTENTIALS ON HIGH POTENTIAL SIDE AND LOW POTENTIAL SIDE~~

~~47, 55: FIRST AND SECOND DIFFERENTIAL AMPLIFIERS~~

~~48: FIRST REFERENCE POTENTIAL~~

~~100: OUTPUT CIRCUIT~~

20 ~~101: SWITCHING CIRCUIT~~

~~102: REFERENCE POTENTIAL GENERATING CIRCUIT~~

~~300: DIFFERENTIAL DRIVE CIRCUIT FOR LOW VOLTAGE~~

~~DIFFERENTIAL SIGNALS~~

~~400: EMPHASIS CIRCUIT~~

25 ~~401, 402: FIRST AND SECOND CIRCUIT GROUPS~~

~~R1-R3, Rp1, Rpn, Rn1, Rnn: RESISTOR~~

~~P1-Pn, N1-Nn: TRANSISTOR~~

~~CMC: CURRENT MIRROR CIRCUIT~~

~~LN+: POSITIVE SIDE OF DRIVE CIRCUIT DIFFERENTIAL  
INPUT SIGNAL~~

~~IN: NEGATIVE SIDE OF DIFFERENTIAL INPUT SIGNAL  
5 TO DRIVE CIRCUIT~~

~~EMP+: POSITIVE SIDE OF DIFFERENTIAL INPUT SIGNAL  
TO EMPHASIS CIRCUIT~~

~~EMP-: NEGATIVE SIDE OF DIFFERENTIAL INPUT SIGNAL  
TO EMPHASIS CIRCUIT~~

~~10 OUT+: POSITIVE SIDE OF OUTPUT FROM HIGH OUTPUT  
DIFFERENTIAL DRIVE CIRCUIT~~

~~OUT-: NEGATIVE SIDE OF OUTPUT FROM HIGH OUTPUT  
DIFFERENTIAL DRIVE CIRCUIT~~

~~HIZ: HIGH IMPEDANCE~~

15 DETAILED DESCRIPTION OF THE PRESENTLY  
~~BEST MODE FOR CARRYING OUT THE INVENTION~~ PREFERRED  
EMBODIMENTS  
[First Embodiment]

A first embodiment of a differential drive circuit  
for low voltage differential signals according to the  
20 present invention will be described by using FIG. 1.  
FIGURE 1 is a circuit block diagram that describes a  
configuration of the differential drive circuit for low  
voltage differential signals of the present invention. A  
differential drive circuit 300 for low voltage differential  
25 signals of the present invention is constituted by an  
output circuit 100 in compliance with the LVDS interface  
standard (IEEE P1596, 3) and a reference voltage generating

potential

circuit 102.

The output circuit 100 is constituted by a switching circuit 101 which receives differential signals inputted to and outputs current signals to a terminating resistor RL; a PMOS transistor 2 which is connected at its one end to a power supply potential 14 on the low potential side and at its other end to a node 12 in the switching circuit 101 and operates as a source follower; and an NMOS transistor 1 which is connected at its one end to a power supply potential 13 on the high potential side and at its other end to a node 11 in the switching circuit 101 and operates as a source follower.

The switching circuit 101 is constituted by NMOS transistors 3 through 6, and drains of the transistors 3 and 5 are commonly connected to a source of the transistor 1, forming the node 11. Sources of the transistors 4 and 6 are commonly connected to a source of the PMOS transistor 2, forming the node 12. A node 8, which is a connection point at which the transistors 3 and 4 are connected in series and a node 7, which is a connection point at which the transistors 5 and 6 are connected in series, form output terminals of the output circuit 100. A node 9, which is a connection point at which the transistors 3 and 6 are commonly connected at their gates and a node 10, which is a connection point at which the transistors 5 and 4 are connected at their gates, form input terminals. The input terminals of the nodes 9 and 10 are inputted thereto with

differential signals, which are inverse of each other and are oscillated to the power supply ~~voltage~~ <sup>potential</sup> on the low potential side and to the power supply potential on the high potential side. The external terminating resistor  $R_L$  is connected between the nodes 7 and 8.

Provided that the potential of the node 8 is  $V_1$  and the potential of the node 7 is  $V_2$ , the differential potential VOD of outputs can be expressed by  $VOD = V_1 - V_2$ . The offset voltage VOC of the outputs can be expressed by  $VOC = (V_1 + V_2) / 2$ . In this configuration, when reference potentials generated by the reference potential generating circuit 102 are inputted to gates of the NMOS transistor 1 and the PMOS transistor 2, because all transistors have a source follower configuration, the potential of the node 11 and the potential of the node 12 are determined. At this stage, it is indicated that the voltage which is generated by the reference potential generating circuit 102 and applied to the gate of the NMOS transistor 1 is  $V_3$ , the voltage applied to the gate of the PMOS transistor 2 is  $V_4$ , the potential of the node 11 is  $V_5$ , and the potential of the node 12 is  $V_6$ . Provided that the current flowing through the terminating resistor  $R_L$  is  $I_1$ , when  $I_1$  is small and the NMOS transistor 1 and the PMOS transistor 2 operate in a saturation region, then  $I_1 = \beta_n (V_3 - V_5 - V_{thn})^2 / 2 = \beta_p (V_6 - V_4 - V_{thp})^2 / 2$ . Here,  $\beta_n$  and  $\beta_p$  and  $V_{thn}$  and  $V_{thp}$  are the  $\beta$  values and threshold voltages of the NMOS transistor and PMOS transistor, respectively. Then, formulae of  $VOD = I_1 \times R_L$



and  $VOD \doteq V5 - I1 \times RL / 2 \doteq V6 + I1 \times RL / 2$  are established. The reference potentials  $V3$  and  $V4$  are determined such that the values  $VOC$  and  $VOD$  become target values. According to the LVDS standard, the standard value for  $VOC$  is 1.2V, the standard value for  $VOD$  is 250mV, and the <sup>standard</sup> value for  $RL$  is 100 $\Omega$ . An example is provided in which the reference potentials  $V3$  and  $V4$  are determined such that  $VOC$  and  $VOD$  for the above case become target values. For the simplicity sake, it is assumed that  $\beta_n = \beta_p = 2$  and  $V_{thn} = V_{thp} = 0.5$ . From this, a calculation can be done with  $V3 = 1.2 + 0.250 / 2 + 1 = 2.45V$  and  $V4 = 1.2 - 0.25 / 2 - 1 = 0.12V$ . Here, attention should be directed to the fact that the  $\beta$  values of the switching transistors 3 to 6 are made to be large so that the ON resistance is sufficiently small. Note that the switching circuit 101 can also be configured as a CMOS circuit, which uses NMOS and PMOS transistors.

FIGURE 2 is a circuit diagram, which describes the embodiment of the reference potential generating circuit 102 according to the present invention. The reference potential generating circuit 102 is constituted by a resistor  $R1$  connected at its one end to a first power supply potential 13 on the high potential side; a resistor  $R3$  connected at its one end to a second power supply potential 14 on the low potential side; and a resistor  $R2$  connected to the  $R1$  and the  $R3$  in series. A connection node 21 between the  $R1$  and the  $R2$  is connected to the gate of the NMOS transistor 1 in the output circuit 100 and



supplies a reference potential V3. A connection node 22 between the R2 and the R3 is connected to the gate of the PMOS transistor 2 in the output circuit 100 and supplies a reference potential V4. FIGURE 3 is a diagram, which shows a reference potential generating circuit having variable resistors for changing resistors R1 and R3. By changing the resistors R1 and R3, the differential potential is changed with the offset potential being constant. Provided that the potential of a first power supply potential 13 on the high potential side is VDD, the potential of a second power supply potential 14 on the low potential side is VSS, the potential of a node 21 is V21, the potential of a node 22 is V22, and the sum of resistance values  $R1+R2+R3$  is R, V21 and V22 can be expressed by  $V21=(VDD-VSS) \times (R2+R3)/R$  and  $V22=(VDD-VSS) \times (R3)/R$ . When the ratio of the gate width to the gate length of each of the NMOS transistor 1 and the PMOS transistor 2 is adjusted in such a manner that currents which flow due to voltages appearing between the respective gates and sources are equal and  $R3=R1$ , the offset potential will be defined by the formula of  $VOC=(VDD+VEE)/2$ . In this state, the differential voltage VOD moves with the differential potential between the nodes 21 and 22.

FIGURE 4 is a diagram showing a reference potential generating circuit having a potential variable means. The reference potential generating circuit 102 is composed of a first circuit group 301; a second circuit

group 302; and a resistor R2 connected in series between the first circuit group 301 and the second circuit group 302. The first circuit group 301 is configured such that a plurality of PMOS transistors P1 to Pn are connected at  
5 their source sides to a power supply potential 13 on the high potential side, and a plurality of resistors Rp1 to Rpn are connected at their one ends to the drain sides of the plurality of PMOS transistors P1 to Pn, respectively, and at their other ends to a node 21. The second circuit  
10 group 302 is configured such that a plurality of NMOS transistors N1 to Nn are connected at their source sides to a power supply potential 14 on the low potential side, and a plurality of resistors Rn1 to Rnn are connected at their one ends to the drain sides of the plurality of NMOS  
15 transistors N1 to Nn, respectively, and at their other ends to a node 22. Each PMOS transistor and resistor in the first circuit group and each NMOS transistor and resistor in the second circuit group are paired with each other, and the resistance values of a combination of the resistors Rp1  
20 and Rn1 and a combination of the resistors Rpn and Rnn are equally set. Here, the combined resistance value of the resistors Rp1 through Rpn is controlled by the gates of the transistors in the first circuit group and the combined resistance value of the resistors Rn1 through Rnn is  
25 controlled by the gates of the transistors in the second circuit group, whereby VOD can be changed with VOC being constant.

FIGURE 5 is a diagram showing a reference potential generating circuit having another potential variable means. A reference potential generating circuit 102 includes a first circuit group 401 and a second circuit group 402. The first circuit group 401 is composed of an NMOS transistor 41 connected at its drain to a power supply potential 13 on the high potential side and having a gate width which is  $1/n$  of that of the NMOS transistor 1 in FIG. 1; an NMOS transistor 42 connected at its drain to a source of the NMOS transistor 41 and at its gate to the power supply potential 13 and having a gate width which is  $1/n$  of that of the MOS transistors 3 and 5; resistors 45 and 46 connected in series to a source of the NMOS transistor 42 and having a resistance value which is  $n/2$  of that of the terminating resistor  $R_L$ ; an NMOS transistor 43 connected at its drain to the other terminal of the resistor 46 and at its gate to the power supply potential 13 and having a gate width which is  $1/n$  of that of the MOS transistors 4 and 6; an NMOS transistor 44 connected at its drain to a source of the NMOS transistor 43, at its source to a power supply potential 14 on the low potential side, and at its gate to a current mirror circuit CMC; and a differential amplifier 47 having a non-inverting input terminal to which is connected a first reference potential 48 that controls the gate potentials of the NMOS transistor 41 and an NMOS transistor 49. An inverting input terminal of the differential amplifier 47 is connected to a connection

point between the resistors 45 and 46.

The second circuit group 402 is constituted by an NMOS transistor 49 connected at its drain to the power supply potential 13 on the high potential side and having a gate width which is  $1/n$  of that of the NMOS transistor 1 in FIG. 1; an NMOS transistor 50 connected at its drain to a source of the NMOS transistor 49 and at its gate to the power supply potential 13 and having a gate width which is  $1/n$  of that of the MOS transistors 4 and 6; resistors ~~54~~ 53 and 54 connected in series to a source of the NMOS transistor 50 and having a resistance value which is  $n/2$  of that of the terminating resistor  $R_L$ ; an NMOS transistor 51 connected at its drain to the other terminal of the resistor 54 and at its gate to the power supply potential 13 and having a gate width which is  $1/n$  of that of the MOS transistors 4 and 6; a PMOS transistor 52 connected at its source to a source of the NMOS transistor 51 and at its drain to the power supply potential 14 on the low potential side and having a gate <sup>width</sup> which is  $1/n$  of that of the PMOS transistor 2; and a differential amplifier 55 having a non-inverting input terminal to which is connected a reference potential 56 that controls the gate potential of the PMOS transistor 52. An inverting input terminal of the differential amplifier 55 is connected to a connection point between the resistors 53 and 54.

The differential amplifier 47 controls the potential of a node at which the resistors 45 and 46 are

connected, such that the potential approximates the  
reference potential 48 connected to the differential  
amplifier 47. The differential amplifier 55 controls the  
potential of a node at which the resistors 53 and 54 are  
5 connected, such that the potential approximates the  
reference potential 56 connected to the differential  
amplifier 55. The differential potential of outputs is the  
potential difference between the nodes 8 and 7 and the  
current  $I$  flowing through the terminating resistor  $R_L$ , and  
10 thus is represented by  $V_{OD}=I \times R_L$ . Here, a current of  $I/n$   
flows through the NMOS transistors 41 and 49 in the  
reference potential generating circuit 102. The potential  
difference appearing between a connection node of the NMOS  
transistor 42 and the resistor 45 and a connection node of  
15 the resistor 46 and the NMOS transistor 43 and the  
potential difference appearing between a connection node of  
the NMOS transistor 50 and the resistor 53 and a connection  
node of the resistor 54 and the NMOS transistor 51 are  
represented by  $I/n \times (nR_L/2 + nR_L/2) = I \times R_L$ . The current  $I/n$   
20 flowing through the NMOS transistor 44 is determined such  
that the value of  $I \times R_L$  becomes a target value. The offset  
potential  $V_{OC}$  of the outputs can be expressed, using the  
potential  $V_1$  of the node 8 and the potential  $V_2$  of the node  
7, by the formula of  $V_{OC}=(V_1+V_2)/2$ . The offset potential  
25  $V_{OC}$  moves with the potentials of the node 57 at which the  
resistors 45 and 46 are connected and the node 58 at which  
the resistors 53 and 54 are connected. Therefore, the

offset potential VOC is determined by setting the reference potentials 48 and 56 such that the potentials of the nodes 57 and 58 become target values. As such, the differential voltage VOD can be changed with the offset potential VOC being kept constant.

As described above, in the present invention, since the voltage V3 supplied to the gate of the NMOS transistor 1 and the voltage V4 supplied to the gate of the PMOS transistor 2 can be supplied without the need for a differential amplifier, the power consumption is small and the circuit area does not increase. Furthermore, since control can be performed without using a differential amplifier, a configuration resistant to oscillation caused by power supply noise is obtained and the load drive capability is also high.

[Second Embodiment]

A second embodiment of a differential drive circuit for low voltage differential signals according to the present invention will be described by using FIG. 6. FIGURE 6 is a circuit block diagram that describes a configuration of a high output differential drive circuit of the present invention. A differential drive circuit 300 for low voltage differential signals of the present invention is constituted by an output circuit 100, an emphasis circuit 300, and a bias circuit (not shown) for the circuits, for example, a reference potential generating circuit 102.

The ~~drive~~ <sup>output</sup> circuit 100 is a circuit described in FIG. 1. In the emphasis circuit 400, a drain of a PMOS transistor 61 is connected to a node 71 in a switching circuit for the emphasis circuit composed of MOS

5 transistors, to which are inputted differential signals different from those inputted to the ~~drive~~ <sup>output</sup> circuit 100 and which outputs current signals. A source of the PMOS transistor 61 is connected to a power supply on the high potential side 13, and furthermore, a gate of the PMOS

10 transistor 61 is connected to one terminal 67 of a bias power supply (not shown) for the emphasis circuit. In addition, a drain of an NMOS transistor 62 is connected to a node 72 in the switching circuit for the emphasis circuit.

A source of the NMOS transistor 62 is connected to

15 a power supply 14 on the low potential side, and furthermore, a gate of the NMOS transistor 62 is connected to the other terminal 68 of the bias power supply for the emphasis circuit.

The switching circuit for the emphasis circuit is

20 the same circuit as the switching circuit 101 of FIG. 1. The NMOS transistors 63 and 65 are connected to each other at their drains, forming the node 71 and the NMOS transistors 64 and 66 are connected to each other at their sources, forming the node 72. The NMOS transistors 63 and

25 64 and the NMOS transistors 65 and 66 are connected to each other at their sources and drains, forming nodes 73 and 74, respectively. The gates of the NMOS transistors 63 and 66



are connected to a differential signal output terminal on the positive side 69 (~~not shown~~) and the gates of the NMOS transistors 64 and 65 are connected to a differential output terminal on the negative side ~~[[20]]~~<sup>20</sup>. A node 8 in the drive ~~circuit~~<sup>output</sup> 100 and the node 73 in the emphasis circuit 400, and a node 7 in the drive ~~circuit~~<sup>output</sup> 100 and the node 74 in the emphasis circuit 400 are connected to each other, forming output terminals ~~[[21]]~~<sup>21</sup> and ~~[[22]]~~<sup>22</sup> of the high output differential drive circuit 300, respectively.

FIGURE 7 is a diagram showing, by steps, input/output signal trains for output signals from the high output differential drive circuit 300, which emerge with respect to a positive side of a differential input signal inputted to the drive ~~circuit~~<sup>output</sup> 100 and a positive side of a differential input signal inputted to the emphasis circuit 400.

At step 1 in FIG. 7, when the plus side of the differential input signal inputted to the drive ~~circuit~~<sup>output</sup> 100 and the plus side of the differential input signal inputted to the emphasis circuit 400 in FIG. 6 both have a high potential, the negative sides of their corresponding differential input signals have a low potential. That is, the NMOS transistors 3 and 6 on the drive circuit side are in a switched-on state and the NMOS transistors 4 and 5 are in a switched-off state. Similarly, the NMOS transistors 63 and 66 in the emphasis circuit 400 are in a switched-on state and the NMOS transistors 64 and 65 are in a switched-



off state.

On the other hand, regardless of the steps in FIG. 7, the gates of the NMOS transistor 1 and the PMOS transistor 2 in the ~~drive~~<sup>output</sup> circuit 100 of FIG. 6 are activated by bias voltages, respectively, from the reference potential generating circuit 102, which is a bias power supply for the drive circuit, and operate as source followers. Thus, a constant voltage that is determined by bias voltages of the reference potential generating circuit 102 is generated at the nodes 11 and 12 as an output of a voltage drive. The PMOS transistor 61 and the NMOS transistor 62 in the emphasis circuit 400 are activated through the bias power supply terminals 67 and 68 for the emphasis circuit and by a current source realized by a current mirror or the like. Therefore, it operates as a current-driven circuit which is determined by the current of a bias.

Now, at step 1, the NMOS transistors 3 and 6 in the switching circuit of the ~~drive~~<sup>output</sup> circuit 100 are ON and the NMOS transistors 63 and 66 in the switching circuit of the emphasis circuit 400 are ON, and thus, the potential of the output terminal 8 of the differential drive circuit 300 is at a high level and the potential of the output terminal 7 is at a low level. The high level rapidly rises by the voltage drive of the ~~drive~~<sup>output</sup> circuit 100 and further has a drive capability of supplying a current by the current drive of the emphasis circuit 400 and absorbing stray

capacitance across the long signal line load. Similarly,  
the low level rapidly drops by the voltage drive of the  
drive <sup>output</sup> circuit 100 and further has a drive capability of  
drawing the charge of stray capacitance across the long  
5 signal line load by the current drive of the emphasis  
circuit 300. Since the emphasis circuit 400 is current  
driven, the voltage  $V_{SD}$  between the source and drain of  
each of the PMOS transistor 61 and the NMOS transistor 62  
automatically changes according to an applied load, and  
10 when the drive pulse amplitude of the differential drive  
circuit 300 is increased, it has an equivalent capability  
and thus can perform high-speed drive even when the applied  
load is increased.

At step 2, since the differential signal input to  
15 the switching circuit of each of the drive <sup>output</sup> circuit 100 and  
the emphasis circuit 400 is inverted, the operations of the  
switching circuits are inverted and accordingly the  
potentials of the output terminals 7 and 8 of the  
differential drive circuit 300 are also inverted. At steps  
20 3 and 4, these operations are repeated.

At steps 5 to 7, when the positive side of the  
differential input signal inputted to the drive <sup>output</sup> circuit 100  
in FIG. 6 has a low potential and the positive side of the  
differential input signal inputted to the emphasis circuit  
25 400 has a high potential, the negative sides of their  
corresponding differential input signals have potentials  
which are inverse of the potentials of their corresponding

signals. That is, the NMOS transistors 3 and 6 on the drive circuit side are in a switched-off state and the NMOS transistors 4 and 5 are in a switched-on state. Similarly, the NMOS transistors 63 and 66 in the emphasis circuit 400 are in a switched-on state and the NMOS transistors 64 and 65 are in a switched-off state.

Now, at steps 5 to 7, the NMOS transistors 3 and 6 in the switching circuit of the ~~drive~~<sup>output</sup> circuit 100 are OFF and the NMOS transistors 63 and 66 in the switching circuit of the emphasis circuit 400 are ON. Thus, the potential of the output terminal 8 of the differential drive circuit 300 has a value obtained by increasing the voltage which is determined by the voltage drive of the PMOS transistor 2 in the ~~drive~~<sup>output</sup> circuit 100, by an amount equal to the current flowing through the PMOS transistor 61 in the emphasis circuit 400. On the other hand, the potential of the output terminal 7 has a value obtained by reducing the voltage which is determined by the voltage drive and is the voltage of the NMOS transistor 1 in the ~~drive~~<sup>output</sup> circuit 100, by an amount equal to the current flowing through the NMOS transistor 62 in the emphasis circuit 400. Accordingly, as shown by output waveforms in FIG. 7, the amplitude is reduced and a stable potential is set and thus a stable common-mode voltage can be obtained, making it possible to prevent trouble of EMI.

FIGURE 8 is a diagram showing other input/output signal trains. Now, at step 1, the NMOS transistors 3 and

6 in the switching circuit of the ~~drive~~<sup>output</sup> circuit 100 are ON and the NMOS transistors 63 and 66 in the switching circuit of the emphasis circuit 400 are ON, and thus, the potential of the output terminal 8 of the differential drive circuit 300 is at a high level and the potential of the output terminal 7 is at a low level. The high level rapidly rises by the voltage drive of the ~~drive~~<sup>output</sup> circuit 100 and furthermore a current is supplied by the current drive of the emphasis circuit 400; similarly, the low level rapidly drops by the voltage drive of the ~~drive~~<sup>output</sup> circuit 100 and furthermore, a current is supplied by the current drive of the emphasis circuit 300, whereby the amplitude is increased more than that at normal time. By this, even when the signal lines are long and the high-frequency components of signals are attenuated, since the amplitude is increased in advance, a certain signal quality can be maintained. In addition, since the emphasis circuit 400 is current driven, when the output current is  $I$  and the switch resistance of a group of switching transistors for the drive circuit is  $R_{sw}$ , by the current drive, the amplitude can be increased by an amount equal to  $R_{sw}I$ .

At step 2, since the differential signal input to the switching circuit of each of the ~~drive~~<sup>output</sup> circuit 100 and the emphasis circuit 400 is inverted, the operations of the switching circuits are inverted and accordingly, the potentials of the output terminals 7 and 8 of the differential drive circuit 300 are also inverted. At steps

3 and 4, these operations are repeated.

At steps 5 to 7, all differential input signals inputted to the ~~drive~~ <sup>output</sup> circuit 100 of FIG. 6 are low. That is, the NMOS transistors 3 and 6 on the drive circuit side are in a switched-off state and the NMOS transistors 4 and 5 are in a switched-on state. Similarly, the NMOS transistors 63 to 66 in the emphasis circuit 400 are in a switched-off state.

Now, at steps 5 to 7, the NMOS transistors 3 and 6 in the switching circuit of the ~~drive~~ <sup>output</sup> circuit 100 are OFF and the NMOS transistors 63 to 66 in the switching circuit of the emphasis circuit 400 are OFF. Therefore, the potential of the output terminal 8 of the differential drive circuit 300 is determined only by the ~~drive~~ <sup>output</sup> circuit 100 and thus the amplitude does not increase. When the emphasis circuit is ON, as compared with when it is OFF, the high level is increased by an amount equal to  $R_{sw}I$  and the low level is reduced by an amount equal to  $R_{sw}I$ . Accordingly, the common-mode voltage does not change in either case and thus a stable common-mode voltage can be obtained, making it possible to prevent trouble of EMI.

FIGURE 9 is a diagram showing input/output signal trains for a third embodiment in which the PMOS transistor 61 and the NMOS transistor 62 in the emphasis circuit 400 of FIG. 6 are respectively replaced with transistors of the same type as the NMOS transistor 1 and the PMOS transistor 2 in the ~~drive~~ <sup>output</sup> circuit 100, and made to serve as source

followers.

At steps 1 to 4 in FIG. 9, a differential input signal inputted to the emphasis circuit 400 is high impedance. Thus, the potentials of the respective output terminals 7 and 8 of the differential ~~drive~~ <sup>output</sup> circuit 300 are determined by the drive voltage of the drive circuit 100. In this case, a unique circuit design is made possible in which the drive circuit 100 is separated from the emphasis circuit 400 so as to obtain high potential outputs according to the circuit load. At steps 5 to 7, the differential input signal inputted to the ~~drive~~ <sup>output</sup> circuit 100 is high impedance. Thus, the potentials of the output terminals 7 and 8 of the differential drive circuit 300 are determined by the drive voltage of the emphasis circuit 400. In this case too, similarly, it is possible to set a constant voltage in a standby state according to the circuit load by separating the emphasis circuit 400 from the ~~drive~~ <sup>output</sup> circuit 100. The operation can be read as in the case of FIG 7.

As described above, in the present invention, by an emphasis means of increasing the amplitude at a transmitting end by current injection the drive capability of outputs is improved, and by voltage drive the common-mode level is stabilized, whereby the occurrence of trouble of EMI can be reduced; therefore, although the circuit is used for low voltage differential signals, high-speed long-distance drive is made possible.

~~INDUSTRIAL APPLICABILITY~~

A differential drive circuit for low voltage differential signals of the present invention can be  
5 applied not only to an LVDS interface but also to the differential drive circuit itself.

CLAIMS

1. A differential drive circuit for low voltage differential signals, comprising:

5 a switching circuit composed of MOS transistors, and configured to be inputted thereto with differential signals and to output current signals;

an output circuit including an NMOS transistor connected at its one end to a power supply potential on a high potential side and at its other end to one node in the switching circuit, and operating as a source follower; and a PMOS transistor connected at its one end to a power supply potential on a low potential side and at its other end to other node in the switching circuit and operating as a source follower; and

a reference potential generating circuit that supplies reference potentials to gates of the NMOS transistor and the PMOS transistor, respectively, wherein

the reference potential generating circuit includes potential variable means for changing a differential potential with an offset potential being kept constant.

2. The differential drive circuit for low voltage differential signals according to claim 1, wherein

the switching circuit includes: a first transistor and a second transistor connected at their one ends to a



source of the NMOS transistor, forming a node; and a third transistor and a fourth transistor connected at their one ends to a source of the PMOS transistor, forming a node,

5 a node at which the first transistor and the third transistor are connected at their other ends and a node at which the second transistor and the fourth transistor are connected at their other ends form output terminals of the output circuit, and

10 a node at which the first transistor and the fourth transistor are connected at their gates and a node at which the second transistor and the third transistor are connected at their gates form input terminals for the differential signals.

15 3. The differential drive circuit for low voltage differential signals according to claim 1, wherein the reference potential generating circuit includes:

a first resistor connected between the power supply potential on the high potential side and the gate of  
20 the NMOS transistor;

a second resistor connected between the gate of the NMOS transistor and the gate of the PMOS transistor;  
and

a third resistor connected between the gate of the PMOS transistor and the power supply potential on the low potential side.

4. The differential drive circuit for low voltage differential signals according to claim 3, wherein the first resistor and the third resistor in the reference potential generating circuit have an equal resistance value.

5

5. The differential drive circuit for low voltage differential signals according to claim 1, wherein the reference potential generating circuit includes:

10 a first circuit group composed of a plurality of PMOS transistors connected in series and a plurality of resistors connected in series, which are connected in parallel;

15 a second circuit group composed of a plurality of NMOS transistors connected in series and a plurality of resistors connected in series, which are connected in parallel; and

20 a resistor connected between the resistors in the first circuit group and the resistors in the second circuit group, and wherein the resistors in the first circuit group and the resistors in the second group are set to an equal resistance value, the resistance value being changeable by controlling gates of the transistors in the first and the second circuit groups.

25

6. The differential drive circuit for low voltage differential signals according to claim 1, wherein the

reference potential generating circuit includes:

a first circuit group further including:

a first NMOS transistor connected at its drain  
to the power supply potential on the high potential side;

5 a second NMOS transistor connected at its drain  
to a source of the first NMOS transistor and at its gate to  
the power supply potential on the high potential side;

a third NMOS transistor connected at its source  
to the power supply potential on the low potential side;

10 a fourth NMOS transistor connected at its  
source to a drain of the third NMOS transistor and at its  
gate to the power supply potential on the high potential  
side;

a first resistor and a second resistor  
15 connected between a source of the second NMOS transistor  
and a drain of the fourth NMOS transistor;

a first differential amplifier having an output  
terminal connected to gates of the first NMOS transistor  
and a fifth NMOS transistor and controlling potentials of  
20 the gates, and operating such that a potential of a node at  
which the first resistor and the second resistor are  
connected approximates a first reference potential; and

the current source variable means that controls  
a current of the third NMOS transistor connected at its  
25 source to the power supply potential on the low potential  
side; and

a second circuit group further including:

the fifth NMOS transistor connected at its drain to the power supply potential on the high potential side;

5 a sixth NMOS transistor connected at its drain to a source of the fifth NMOS transistor and at its gate to the power supply potential on the high potential side, and a seventh PMOS transistor connected at its drain to the power supply potential on the low potential side;

10 an eighth NMOS transistor connected at its source to a source of the seventh PMOS transistor and at its gate to the power supply on the high potential side, and a third resistor and a fourth resistor connected between a source of the sixth NMOS transistor and a drain of the eighth NMOS transistor; and

15 a second differential amplifier having an output terminal connected to a gate of the seventh PMOS transistor and controlling a potential of the gate, and operating such that a potential of a node at which the third resistor and the fourth resistor are connected  
20 approximates the first reference potential.

7. The differential drive circuit for low voltage differential signals according to claim 6, wherein resistance values of the first resistor, the second  
25 resistor, the third resistor, and the fourth resistor in the reference potential generating circuit are  $n/2$  ( $n$  is a positive integer value) times a resistance value of a

terminating resistor connected to output terminals of the output circuit.

8. The differential drive circuit for low voltage differential signals according to claim 6, wherein

a size of the first NMOS transistor and that of the fifth NMOS transistor in the reference potential generating circuit are  $1/n$  ( $n$  is a positive integer value) of a size of the NMOS transistor, respectively, and

a size of the seventh PMOS transistor is  $1/n$  ( $n$  is a positive integer value) of a size of the PMOS transistor.

9. The differential drive circuit for low voltage differential signals according to claim 1,

wherein output terminals of the output circuit are connected to output terminals of an emphasis circuit,

wherein the emphasis circuit includes a switching circuit for the emphasis circuit constituted by MOS transistors, which are inputted thereto with different differential signals, and output current signals, one node in the switching circuit for the emphasis circuit being connected to a drain of a PMOS transistor, a source of the PMOS transistor connected to the power supply potential on the high potential side, and a gate of the PMOS transistor connected to one terminal of a bias power supply for the emphasis circuit, and

wherein the other node in the switching circuit

for the emphasis circuit is connected to a drain of an NMOS transistor, a source of the NMOS transistor being connected to the power supply on the low potential side, and a gate of the NMOS transistor being connected to the other  
5 terminal of the bias power supply for the emphasis circuit.

10. The differential drive circuit for low voltage differential signals according to claim 9, wherein the switching circuit for the emphasis circuit is the switching  
10 circuit according to claim 2.

11. The differential drive circuit for low voltage differential signals according to claim 9, wherein the emphasis circuit is configured in such a manner that:  
15 one node in the switching circuit for the emphasis circuit is connected to a source of an NMOS transistor, a drain of the NMOS transistor is connected to the power supply on the high potential side, and a gate of the NMOS transistor is connected to one terminal of a bias power  
20 supply for the emphasis circuit; and

the other node in the switching circuit for the emphasis circuit is connected to a source of a PMOS transistor, a drain of the PMOS transistor is connected to the power supply on the low potential side, and a gate of  
25 the PMOS transistor is connected to other terminal of the bias power supply for the emphasis circuit.

12. The differential drive circuit for low voltage differential signals according to claim 11, wherein the switching circuit for the emphasis circuit is the switching circuit according to claim 2.

5

13. An electronic apparatus comprising a differential drive circuit for low voltage differential signals according to any one of claims 1 through 12.

10 14. The electronic apparatus according to claim 13, wherein the electronic apparatus is constituted by a mobile terminal.

ABSTRACT OF THE DISCLOSURE

Provision of a differential drive circuit for low voltage differential signals is made in which the circuit area and current consumption are reduced and the problem of oscillation caused by noise is solved by eliminating differential amplifiers or reducing the number of differential amplifiers and a high drive capability is provided, and an electronic apparatus incorporating such a circuit.

The circuit includes: a switching circuit constituted by MOS transistors, to which differential signals are inputted and which outputs current signals; an output circuit constituted by an NMOS transistor connected at its one end to a power supply potential on the high potential side and at its other end to one node in the switching circuit and operating as a source follower, and a PMOS transistor connected at its one end to a power supply potential on the low potential side and at its other end to other node in the switching circuit and operating as a source follower; and a reference potential generating circuit that supplies reference potentials to gates of the PMOS transistor and the NMOS transistor, respectively, wherein the reference potential generating circuit includes potential variable means for changing a differential potential with an offset potential being constant. The circuit further includes an emphasis circuit for the output



circuit.